High Value
Superior Quality
Performance/Durability
Stylish Design
Heat/Cold Resistance





Features and Specifications



Sunview Patio Doors'

value-priced series starts with the most advanced vinyl. A high-grade resin unmatched for strength, weight reduction and freedom from wear - it will not rot, rust, pit or blister over long periods

of time. Door ships knock down for



Elegant Hardware

Available in standard white and black, with an optional upgrade to satin nickel.



Glazing

High-performance glazing with Low-E glass and Super Spacer® technology.

Super Spacer



Optional Locks

Two-Position Kick Locks mount on the bottom of the operating door. Used as secondary lock when the door is closed and available in white, beige, or brown.

Twin-point Locks provide two heavy-duty locking points on the door frame. Available on all hardware handles.

Optional Decorative Grills

Internal grills are available in a wide range of design styles with colours that include **Flat Grills** in two-tone, white, brass and pewter, Georgian Grills in white, and Pencil Grills in white, brass and pewter.



Frame

- Double perimeter seals
- 47/8" mechanically fastened vinyl frame
- Components easily installed and replaceable
- Stainless steel roller track

Durable Welded Sash


- Reinforced with steel to withstand higher wind loads
- Double perimeter seal for superior air-tightness
- Adjustable nylon tandem ball-bearing rollers
- 1" sealed units for optimal thermal performance

Dimensions Door/Panel Configurations and Finished Sizes















3 Panels

88_{1/2} W x 79_{1/2} H

106_{1/2} W x 79_{1/2} H



4 Panels

116_{1/2} W x 79_{1/2} H 140_{1/2} W x 79_{1/2} H

Optional Exterior Colours

Sunview's patio doors boast a wide range of exterior colour options that feature a durable finish that is also UV stable.



Performance

2 Panels

59_{1/2} W x 79_{1/2} H

71_{1/2} W x 79_{1/2} H

Standard	Configuration	Performance Class and Grade	Air Leakage	Water Penetration Resistance	Design Pressure
AAMA/WDMA/CSA 101/1.S.2/A440-08 and CSA A440S1-09	0X / XO	R·PG30	A3-0.1 L/s-m ²	220 Pa (4.5 psf)	±1920 Pa (±40 psf)









Our products meet the Energy Star program guidelines for helping businesses and individuals protect the environment through superior energy efficiency.

