

Patio doors are a reflection of style and a reflection of luxury. Make the best possible statement with Ply Gem Windows Mira Premium Series. Designed with exquisite craftsmanship and one-of-a-kind details, it can help you bring your unique vision to life. And, because it's a Ply Gem patio door, you can take comfort in knowing that it's built with energy-efficiency and long lasting quality in mind.



GREEN

APPROVED

HINGED PATIO DOOR



PLY GEM MIRA PREMIUM SERIES WINDOWS HAVE BEEN GREEN APPROVED BY THE NAHB RESEARCH CENTER.

This means you can be assured that Ply Gem Mira Premium Series windows comply with specific green practice criteria in the National Green Building Standard. Visit www.GreenApprovedProducts.com for more details.

HINGED PATIO DOOR

		NFRC CERTIFIED		
	R Value	U Factor	SHGC	VT
WITH WARM EDGE				
³/₄" Clear	2.27	0.44	0.36	0.37
	2.86	0.35	0.17	0.32
³/ ₄ " HP ^{sc} Glass	2.94	0.34	0.13	0.25
³/ ₄ " HP2+ Glass	3.13	0.32	0.17	0.31
³/ ₄ " HP2+sc Glass	3.13	0.32	0.13	0.24
WITH WARM EDGE+				
³/4" HP Glass	3.03	0.33	0.17	0.32
³/ ₄ " HP ^{sc} Glass	3.03	0.33	0.13	0.25
³/4" HP2+ Glass	3.23	0.31	0.17	0.31
³/4" HP2+sc Glass	3.23	0.31	0.13	0.24

All units rated in accordance with NFRC 100/200 standards by a NAMI Accredited lab. Performance values reflect the performance of units tested with the following configuration: ¾" IGU, 3mm glass, no grilles and Warm Edge spacer system and Warm Edge+ spacer system.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

Most unit sizes ENERGY STAR® qualified in most zones and may be eligible for LEED for Homes* credits.

*LEED for Homes is a rating system of the U.S. Green Building Council that promotes the design and construction of high-performance green homes.

- 1. Units up to call size 60610 are rated DP50 straight out of the box.
- 2. Coastal hardware is optional

EXTERIOR CLADDING COLOR OPTIONS



NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

STANDARD FEATURES

- Ball bearing hinges standard for smooth operation
- Center mull is integrated into the sill design for higher structural performance
- Adjustable thermally broken sill for increased thermal performance
- Full-perimeter weatherstripping for air-tight performance and smooth operation
- · Multi-point locking system
- 1¾" panels with wide stiles and rails for a true

 French look
- Select clear wood interior ready for paint or stain to match any interior décor (also available in pre-finished white)
- Durable .050 extruded aluminum claddir on exterior surfaces of panels and fram resists dings and dents while providing structural integrity
- Integral face groove allows for easy mulling and exterior accessory application
- AAMA 2604 paint finish provides superior resistance to chalking and fading
- Energy-efficient Warm Edge insulating tempe HP glass (Low-E/argon gas fill) reduces energ costs while reducing fabric fading





OPTIONS

GLASS OPTIONS:

HP, HPsc, HP2+, HP2+sc, Warm Edge+, tinted, obscure and laminated

GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in $^5/_8$ " and $^7/_8$ " flat, $^5/_8$ " sculptured and 1" contoured (the latter in white only); simulated-divided-lite (SDL) available in $^7/_8$ " and $^11/_4$ "; $^7/_8$ " full surround removable wood grilles

EXTERIOR CASING:

J Channel, 180 Brick Mould, 31/4" Williamsburg, 31/2" Flat

JAMBS WIDTHS:

 $4^9\!/_{16}"$ and $6^9\!/_{16}"$ full-width jambs in pre-finished white or natural "clear" wood

HARDWARE OPTIONS:

Bright brass, antique brass, satin nickel and o rubbed bronze, two-way adjustable hinges

PRODUCT CONFIGURATION:

Transoms, circle heads, ellipticals, arches, side lites and various architectural shapes



