

2900 Hybrid Aluminum/Vinyl Series



All framing constructed with superior thermal performance

Exterior aluminum strength with a warm vinyl interior

Narrow sight lines maximize view

Slim frames complement modern architectural styles

Durable factory-applied colour options

Easy to install pre-fabricated knockdown kits

Frame depths 5^{7/8}" with optional extensions

EFFICIENCY. QUALITY. HIGH VALUE.

2900 Hybrid Aluminum/Vinyl Series

The 2900 Hybrid Series Aluminum/Vinyl Patio Door

Innovative **2900 Hybrid Series** patio doors offer superior thermal and structural advantages. They provide a level of performance unparalleled in aluminum sliding doors. Enjoy lower maintenance with Sunview engineered quality, styling and beauty. Plus, enhanced insulation helps conserve energy and helps your heating bills in cold weather. Aluminum doors also play a vital role in controlling temperatures in the summer.

Choose the **2900 Hybrid Series** patio door for strength, lasting value, improved thermal technology, and a wide range of flexible configurations.





Performance

- U-factor of 1.02 W/m².K (0.18 Btu/hr.ft².°F) with triple-glazing and argon fill
- Standard dual glazed product meets Energy Star® Zone 1,2
- Meets the structural performance requirements at DP 80 (±3840 Pa)
- Provides water resistance at 580 Pa (12 psf) equal to driving rain at 115 Km/h (71 mph)

www.sunviewdoors.com

Features and Options

Hardware Options

Stylish white or black contemporary handles with a single-point lock come standard. Optional twin-point key locks, and a satin nickel handle finish are also available.

Elegant heavy duty screen

Pocket covers on interior. exterior jambs and sill

1" or 1^{3/8}" insulated glass

Single-point locking system

Whisper quiet rollers

Multi-chamber frame and sill

5^{7/8}" frame and sill

Mechanical frame and sash





Finish

Standard single-point locking system

Optional Security Locks



Two Position Kick Locks mount on the bottom of the operating door. Used as secondary lock. Available in white, beige or brown.



Guardian Locks mount on the top of the operating door; security bolt locks into the frame. Available in white, beige or brown.



Folding Security Bars mount on the fixed side of the door frame and swing down to stop the door from operating.

Optional Exterior Colours

Colours Sunview's patio doors boast a wide range of exterior colour options that feature a durable finish that is also UV stable.

Insulating Glass

One-inch tempered sealed insulating glass, or upgrades to 13/8" tripleglazed argon-filled Low-E coated glass for greater energy performance and cold climate condensation resistance. Colour tinted or reflective glass meets the most demanding architectural specifications.

Super Spacer®

Stays cool in summer



www.sunviewdoors.com





2900 Hybrid Aluminum/Vinyl Series

3 Panels

Dimensions Door/Panel Configurations and Finished Sizes (Exterior view)

2 Panels






OXO-Slide R to L or OZO-Slide L to R


Product Code	Frame Size	
50610	59 x 81 1/2	
60610	71 x 81 1/2	
80610	95 x 81 1/2	

Product Code	Frame Size	
76610	881/2 x 81 1/2	
90610	1061/2 x811/2	
120610	1421/2 x811/2	





4 Panels



OXXO-Slide R and Slide L from Centre

Product Code	Frame Size
100610	117 x 81 1/2
120610	141x811/2
160610	189 x 81 1/2

Performance 2900 Hybrid Patio Door meets NAFS/Class R-PG80 Type SD

Standard	Air	Water Penetration	Design
	Leakage	Resistance	Pressure
AAMA/WDMA/CSA 101/I.S.2/A440-11	A3	580 Pa (12 psf)	±3840 Pa (80.20 psf)

Distributed by:





www.sunviewdoors.com